

imageRUNNER ADVANCE 6575i/6565i 6555i

imageRUNNER ADVANCE 6500 III Series

Black-and-White | Mid- to High-Volume | Multifunction

Print up to 75 ppm (BW)

Scan up to 240/220 ipm (300 dpi) (BW/color, duplex)

Print up to 11" × 17"

7,700-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.²

QUALITY AND RELIABILITY

X

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.³
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.

SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR[®] certified and rated EPEAT[®] Gold.⁴

CONFIGURATION OPTIONS



Main Unit

Type

Monochrome Laser Multifunctional **Core Functions**

Standard: Print, Copy, Scan, Send, Store Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel Standard:

10.1" TFT LCD WSVGA Color Flat- panel 10.4" TFT LCD SVGA Color Upright-panel

Optional Memory 3.0 GB RAM

Hard Dick Drive

I III II DISK DITVE	
Standard:	250 GE
Maximum	1 TB

Interface Connection

Network	

Standard:	1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
Optional:	NFC, Bluetooth Low Energy
Others	
Standard:	USB 2.0 x2 (Host), USB 3.0 x1 (Host),
	USB 2.0 x1 (Device)
Optional:	Serial Interface, Copy Control Interface
Paper Capacity	

Capacity

Standard:	4,200 Sheets
Maximum:	7,700 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard:	Dual 1,500-sheet Paper Drawers, Dual
	550-sheet Paper Cassettes, 100-sheet
	Stack Bypass
Optional:	3,500-sheet Paper Deck
	(POD DECK LITE-C1 or
	PAPER DECK UNIT-E1)

Paper Output Capacity (LTR, 20 lb. Bond)

With Copy Tray:	250 Sheets
With External	3,500 Sheets
Finishers:	

Finishing Capabilities

With External	Collate, Group, Offset, Staple, Staple
Finishers:	On Demand, Staple-free Staple, Booklet,
	Hole Punch, Document Insertion, C- and
	Z- Folding

Supported Media Types

Paper Drawers	Thin, Plain, Recycled, Color, Heavy,	
(1/2):	Pre-punched, Letterhead, Bond	
Paper	Thin, Plain, Recycled, Color, Heavy,	
Cassettes (3/4):	Pre-punched, Letterhead, Bond, Tab.	
Stack Bypass:	Thin, Plain, Recycled, Color, Heavy,	
	Pre-punched, Bond, Transparency, Labels,	
	Letterhead, Tab, Tracing	
POD DECK	Thin, Plain, Recycled, Color, Heavy, Pre-	
LITE-C1:	punched, Letterhead, Bond, Transparency,	
	Labels, Tab	
PAPER DECK	Thin, Plain, Recycled, Color, Heavy,	
UNIT-E1:	Pre-punched, Letterhead, Bond	
Supported Media Sizes		

Paper Drawers Lette

11" x 17", Legal, Letter, Letter-R, Executive,
Statement-R, Custom Size (5-1/2" x 7-1/8"
to 11-3/4" x 19-1/4")
11" x 17", Legal, Letter, Letter-R, Executive,
Statement-R, Custom Size
(4" x 5-7/8" to 11-3/4" x 19-1/4"), Free Size
(4" x 7-1/8" to 11-3/4" x 19-1/4")
11" x 17", Legal, Letter, Letter-R, Executive,
Statement-R, Custom Size (5-1/2" x 7-1/8"
to 11-3/4" x 19-1/4")
Letter

Supported Media Weights

Paper Decks/	14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Cassettes:	
Stack Bypass:	14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Duplexing:	14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)
Warm-up Time	
From Power On:	Approx. 30 Seconds ²
	2000 13

From Sleep	Approx. 30 Seconds ³
Mode:	
Quick Startup	Approx. 4 Seconds ⁴
Mode:	

Dimensions (W x D x H) 26-3/8" x 30-5/8" x 48"

(670 mm x 779 mm x 1220 mm) Installation Space (W x D)

Basic:	Stack Bypass Extended+ Cassette Drawers
	open + Copy Tray:
	60-3/8" x 53-1/4" (1533 mm x 1353 mm)
Fully	Booklet Finisher + Paper Deck + Insertion
Configured:	and Folding Unit + Puncher Unit + Cassette
-	Drawers open:
	95-7/8" x 53-1/4" (2436 mm x 1353 mm)
Wainht	

Weight

Approx. 515.9 lb. (234 kg)⁵

Print Specifications

Print Speed

6575i III:	Up to 75 ppm (Letter)
	Up to 58 ppm (Letter-R)
	Up to 45 ppm (Legal)
	Up to 37 ppm (11" x 17")
6565i III:	Up to 65 ppm (Letter)
	Up to 50 ppm (Letter-R)
	Up to 39 ppm (Legal)
	Up to 32 ppm (11" x 17")
6555i III:	Up to 55 ppm (Letter)
	Up to 43 ppm (Letter-R)
	Up to 39 ppm (Legal)
	Up to 32 ppm (11" x 17")

Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR III, PCL[®]6, Adobe[®] PS[®] 3

Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access⁶

Supported File Types

PDF, TIFF, JPEG, EPS,⁷ XPS

Printing from Mobile and Cloud

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts PC

PCL Fonts:	93 Roman, 10 Bitmap fonts, 2 OCR
	fonts, Andalé Mono WT J/K/S/T (Japanese,
	Korean, Simplified and Traditional Chinese) ⁸ ,
	Barcode Fonts ⁹
PS fonts:	136 Roman

Operating System¹⁰

operating system	
UFRIII:	Server 2008/Windows 7/Server 2008 R2/ Server 2012/Windows 8.1/Server 2012 R2/
	Windows 10/Server 2016, MAC OS X (10.9 or later)
PCL:	Server 2008/Windows 7/Server 2008 R2/
	Server 2012/Windows 8.1/Server 2012 R2/
	Windows 10/Server 2016
PS:	Server 2008/Windows 7/Server 2008 R2/
	Server 2012/Windows 8.1/Server 2012 R2/
	Windows 10/Server 2016, MAC OS X
	(10.9 or later)
PPD:	MAC OS X (10.3.9 or later), Windows 7 / 8.1/10

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing

Copy Specifications Copy Speed

6575i III:	Up to 75 ppm (Letter) Up to 58 ppm (Letter-R)
6565i III:	Up to 45 ppm (Legal) Up to 37 ppm (11" x 17") Up to 65 ppm (Letter)
	Up to 50 ppm (Letter-R) Up to 39 ppm (Legal)
6555i III:	Up to 32 ppm (11" x 17") Up to 55 ppm (Letter) Up to 43 ppm (Letter-R)
	Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")

First-Copy-Out Time (Letter)

6575i III: As fast as 3.1 seconds As fast as 3.3 seconds 6565i III 6555i III: As fast as 3.3 seconds

Copy Resolution (dpi) Reading: 600 x 600 1200 x 1200 Printing:

Multiple Copies

Up to 9,999 Copies

Magnification

25%-400% (1% Increments)

Preset Reductions 25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on I, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Cascade Copy, Copy ID Card, Detect Feeder Multi Sheet Feed, Free Size Original, Skip Blank Originals

Scan Specifications

Type

Color Platen and Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover

-	(50 to 220 g/m²)
CL Original:	17 lb. Bond to 80 lb. Cover
-	(64 to 220 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: up to 4.4 lb. (2 kg)] Max. Platen

Scanning Size: 11-3/4" x 17" (297 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA Supported OS: Windows 7/8.1/10 Server 2008/Server 2008 R2/Server 2012/ Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning BW: 120 ipm (300 dpi)/120 ipm (600 dpi) Color: 120 ipm (300 dpi)

Double-sided Scanning BW: 240 ipm (300 dpi)/150 ipm (600 dpi) Color: 220 ipm (300 dpi)

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol

File: Email:	FTP, SMB v3.0, WebDAV SMTP, POP3, I-Fax (Simple, Full)
File Format	
Standard:	TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XF

ire), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word) Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications (Optional)

Modem Speed

33.6 Kbps Super G3: G3 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement-R to 11" x 17'

Fax Memory Up to 30,000 Pages Speed Dials

Max. 200

Group Dials/Destinations Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup Yes

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV Windows (Windows 7/8.1/10) Supported Client PC: Concurrent Connections (Max.): SMB: WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD) Approx. 480 GB (With Optional 1 TB HDD)

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

Memory Media Standard: USB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express," User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access Management System Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Verify System at Startup Hard Disk Drive Mirroring, Hard Disk Drive Optional: removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network Standard:

Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document Standard:

Optional:

Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature User Signature, Document Scan Lock

Environmental Specifications

Operating Environment

50 to 86 °F 20 to 80 % RH (Relative Humidity) Temperature: Humidity:

Power Requirements

120-127 V AC, 60 Hz, 16 A

Plug (Main Unit) NEMA 5-20P

Power Consumption

Maximum: Approx. 2,032 W Standby: Approx. 237.3 W12 Sleep mode: 0.9 W¹³ Typical Electricity Consumption (TEC) Rating: iR ADV 6575i III: 6.3 kWh iR ADV 6565i III: 5.8 kWh iR ADV 6555i III: 5.2 kWh

Standards

ENERGY STAR® Certified Rated EPEAT® Gold¹⁴

Consumables

Toner

GPR-38 Black Toner

Toner Yield (Estimated @ 6% Coverage)

56,000 Images

- ¹ Some types of tracing paper cannot be used. ² Time from device power-on, until copy ready (not print
- reservation). ³ Time from exiting Sleep mode to when printing is operational.
- ⁴ Time from device power-on to when key operations can be performed on the touch panel.
- Includes Main Unit, ADF, and Consumables
- ⁶ PDF print from Websites is supported.
- ⁷ EPS can be printed directly only from the Remote User Interface.
- Interface. ⁹ Requires the optional PCL International Font Set-AI. ⁹ Requires the optional Barcode Printer Kit-DI. ¹⁰ Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your calor concentrative. sales representative.
- No charge for this solution; however activation is required. ¹² Standby Reference Value: measured one unit.
- ¹³ 0.9 W sleep mode not available in all circumstances due to certain settings.
- ⁴ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE 6500 III Series Specifications document.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of user devices and date. Canon does not surgered that use of its features will accured hourse. Notice No your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All other referenced product names and mark are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors ©2019 Canon U.S.A., Inc. All rights reserved.

To learn about Canon's many awards, visit usa.canon.com/awards.









